

# Introduction to Programming: Lecture 20


K Narayan Kumar

Chennai Mathematical Institute


<http://www.cmi.ac.in/~kumar>

24 October 2013

# Graphs




# Graphs



- Represent edges in the graph as a function

```
type Vert = Int
maxvert = 6
edge :: Vert -> Vert -> Bool
edge 1 2  = True
edge 1 4  = True
...
edge 5 6  = True
edge _ _  = False
```

# Graphs



- Represent edges in the graph as a function

```
type Vert = Int
maxvert = 6
edge :: Vert -> Vert -> Bool
edge 1 2  = True
edge 1 4  = True
...
edge 5 6  = True
edge _ _  = False
```

- Goal: define `reachable :: Vert -> [Vert]`

# Graphs ...

- ▶ Inductive definition of `reachable v`

# Graphs ...

- ▶ Inductive definition of `reachable v`
  - ▶ `v` is reachable from `v`
  - ▶ `x` is reachable from `v` and `edge x y` then `y` is also reachable from `v`.

# Graphs ...

- ▶ Inductive definition of `reachable v`
  - ▶ `v` is reachable from `v`
  - ▶ `x` is reachable from `v` and `edge x y` then `y` is also reachable from `v`.
- ▶ Cannot directly translate this definition into Haskell
- ▶ `extend` picks up the neighbours of a given vertex.

```
extend :: Vert -> [Vert]
```

```
extend v = [w | w <- [1..maxvert], edge v w]
```

# Reachability ...

- Now, vertices reachable from  $v$  can be identified as

```
extendall :: [Vert] -> [Vert]  
extendall = concatMap extend
```



# Reachability ...

- ▶ Now, vertices reachable from `v` can be identified as

```
extendall :: [Vert] -> [Vert]  
extendall = concatMap extend
```

- ▶ Computes all vertices reachable in one step.

# Reachability ...

- ▶ Now, vertices reachable from `v` can be identified as

```
extendall :: [Vert] -> [Vert]
extendall = concatMap extend
```

- ▶ Computes all vertices reachable in one step.
- ▶ Find all vertices reachable in  $\leq$  `maxvert` steps.

# Reachability ...

- ▶ Now, vertices reachable from `v` can be identified as

```
extendall :: [Vert] -> [Vert]
extendall = concatMap extend
```

- ▶ Computes all vertices reachable in one step.
- ▶ Find all vertices reachable in  $\leq$  `maxvert` steps.

```
reachable v = concat (take maxvert
                        (iterate extendall [v]))
```

# Reachability ...

- ▶ Now, vertices reachable from `v` can be identified as

```
extendall :: [Vert] -> [Vert]
extendall = concatMap extend
```

- ▶ Computes all vertices reachable in one step.
- ▶ Find all vertices reachable in  $\leq$  `maxvert` steps.

```
reachable v = concat (take maxvert
                        (iterate extendall [v]))
```

- ▶ There are repetitions at each level.

# Reachability ...

- ▶ Now, vertices reachable from `v` can be identified as

```
extendall :: [Vert] -> [Vert]
extendall = concatMap extend
```

- ▶ Computes all vertices reachable in one step.
- ▶ Find all vertices reachable in  $\leq$  `maxvert` steps.

```
reachable v = concat (take maxvert
                        (iterate extendall [v]))
```

- ▶ There are repetitions at each level.
- ▶ Use `Set` instead of lists.

# Reachability ...

- ▶ Now, vertices reachable from `v` can be identified as

```
extendall :: [Vert] -> [Vert]
extendall = concatMap extend
```

- ▶ Computes all vertices reachable in one step.
- ▶ Find all vertices reachable in  $\leq$  `maxvert` steps.

```
reachable v = concat (take maxvert
                        (iterate extendall [v]))
```

- ▶ There are repetitions at each level.
- ▶ Use `Set` instead of lists.  
or remove duplicates after each level is generated.

# Without Duplicates

```
reachable v = concat (take maxvert  
                      (iterate (remDup.extendall) [v]))
```

# Without Duplicates

```
reachable v = concat (take maxvert  
                      (iterate (remDup.extendall) [v]))
```

where `remDup` removes duplicates in a list.



# Avoiding duplicate expands

- ▶ Vertices repeat at different levels. Can we do better?

# Avoiding duplicate expands

- ▶ Vertices repeat at different levels. Can we do better?
- ▶ Why not **expand** only vertices that have not been expanded already?

# Avoiding duplicate **expands**

- ▶ Vertices repeat at different levels. Can we do better?
- ▶ Why not **expand** only vertices that have not been expanded already?
- ▶ Keep two lists,
  - ▶ one with elements that are reachable and which have been expanded
  - ▶ one with elements that are reachable and which have not been expanded yet.

# Avoiding duplicate **expands**

- ▶ Vertices repeat at different levels. Can we do better?
- ▶ Why not **expand** only vertices that have not been expanded already?
- ▶ Keep two lists,
  - ▶ one with elements that are reachable and which have been expanded
  - ▶ one with elements that are reachable and which have not been expanded yet.
- ▶ In each **iteration** pick an element from the second list.

# Avoiding duplicate **expands**

- ▶ Vertices repeat at different levels. Can we do better?
- ▶ Why not **expand** only vertices that have not been expanded already?
- ▶ Keep two lists,
  - ▶ one with elements that are reachable and which have been expanded
  - ▶ one with elements that are reachable and which have not been expanded yet.
- ▶ In each **iteration** pick an element from the second list.
  - ▶ Expand the element and move it to the first list.
  - ▶ Add all **new** elements in the expansion to the second list.

# Avoiding duplicate **expands**

- ▶ Vertices repeat at different levels. Can we do better?
- ▶ Why not **expand** only vertices that have not been expanded already?
- ▶ Keep two lists,
  - ▶ one with elements that are reachable and which have been expanded
  - ▶ one with elements that are reachable and which have not been expanded yet.
- ▶ In each **iteration** pick an element from the second list.
  - ▶ Expand the element and move it to the first list.
  - ▶ Add all **new** elements in the expansion to the second list.
- ▶ Continue till the second list is empty

# Avoiding duplicate **expands**

- ▶ Vertices repeat at different levels. Can we do better?
- ▶ Why not **expand** only vertices that have not been expanded already?
- ▶ Keep two lists,
  - ▶ one with elements that are reachable and which have been expanded
  - ▶ one with elements that are reachable and which have not been expanded yet.
- ▶ In each **iteration** pick an element from the second list.
  - ▶ Expand the element and move it to the first list.
  - ▶ Add all **new** elements in the expansion to the second list.
- ▶ Continue till the second list is empty

This is the function **step**.

# Avoiding repetition

```
step:: ([Vert], [Vert]) -> ([Vert], [Vert])
step (s,[]) = s
step (s,x:t) = (x:s,nt)
  where
    tmp = extend x
    nt = t ++ filter g tmp
    g y = not (elems y s) && not (elems y t)
```



# Avoiding repetition

```
step:: ([Vert], [Vert]) -> ([Vert], [Vert])
step  (s,[])  =  s
step  (s,x:t) = (x:s,nt)
  where
    tmp = extend x
    nt  = t ++ filter g tmp
    g y = not (elems y s) && not (elems y t)
```

- Iterate `step` to get the answer.

```
iterstep (s,t)
  | (t == []) = (s,[])
  | otherwise = iterstep (step (s,t))
```

```
reachable v = iterstep ([], [v])
```

# Search problems

- ▶ Place  $n$  queens on  $n \times n$  chessboard to not attack each other

# Search problems


- ▶ Place  $n$  queens on  $n \times n$  chessboard to not attack each other
  - ▶ Queens attack along rows, columns and diagonals
  - ▶ Should have exactly one queen on each row and column

# Search problems

- ▶ Place  $n$  queens on  $n \times n$  chessboard to not attack each other
  - ▶ Queens attack along rows, columns and diagonals
  - ▶ Should have exactly one queen on each row and column
- ▶ Naive strategy
  - ▶ Place first queen on leftmost square of first row
  - ▶ In each new row, place queen at leftmost safe square

# Search problems

- ▶ Place  $n$  queens on  $n \times n$  chessboard to not attack each other
  - ▶ Queens attack along rows, columns and diagonals
  - ▶ Should have exactly one queen on each row and column
- ▶ Naive strategy
  - ▶ Place first queen on leftmost square of first row
  - ▶ In each new row, place queen at leftmost safe square
- ▶ After 7 moves we find no safe squares on bottom row



# Backtracking

# Backtracking

- ▶ Go back and try new position for 7th queen

# Backtracking


- ▶ Go back and try new position for 7th queen
- ▶ After all possibilities for 7th queen exhausted, go back and try new position for 6th queen



# Backtracking

- ▶ Go back and try new position for 7th queen
- ▶ After all possibilities for 7th queen exhausted, go back and try new position for 6th queen
- ▶ Similarly go back to 5th queen, 4th queen,  $\dots$ , 1st queen

# Backtracking ...



# Backtracking via Generate and Test

- ▶ In Haskell this can be implemented as follows ...
  - ▶ Represent (partial) placement of queens as a list
  - ▶ Position  $i$  is column number of queen in row  $i+1$   
Earlier board is represented `[1,3,5,7,2,4,6]`

# Backtracking via Generate and Test

- ▶ In Haskell this can be implemented as follows ...
  - ▶ Represent (partial) placement of queens as a list
  - ▶ Position `i` is column number of queen in row `i+1`  
Earlier board is represented `[1,3,5,7,2,4,6]`
- ▶ `extend` computes all ways to extend a placement by one row

# Backtracking via Generate and Test

- ▶ In Haskell this can be implemented as follows ...
  - ▶ Represent (partial) placement of queens as a list
  - ▶ Position  $i$  is column number of queen in row  $i+1$   
Earlier board is represented  $[1,3,5,7,2,4,6]$
- ▶ `extend` computes all ways to extend a placement by one row
- ▶ `extendall` maps `extend` over all placements on  $k$  rows to get all placements on  $k+1$  rows

# Backtracking via Generate and Test

- ▶ In Haskell this can be implemented as follows ...
  - ▶ Represent (partial) placement of queens as a list
  - ▶ Position `i` is column number of queen in row `i+1`  
Earlier board is represented `[1,3,5,7,2,4,6]`
- ▶ `extend` computes all ways to extend a placement by one row
- ▶ `extendall` maps `extend` over all placements on `k` rows to get all placements on `k+1` rows
- ▶ All possible placements of `n` queens
  - ▶ `allqueens n = head (drop n (iterate extendall [[]]))`

# Backtracking via Generate and Test

- ▶ In Haskell this can be implemented as follows ...
  - ▶ Represent (partial) placement of queens as a list
  - ▶ Position  $i$  is column number of queen in row  $i+1$   
Earlier board is represented `[1,3,5,7,2,4,6]`
- ▶ `extend` computes all ways to extend a placement by one row
- ▶ `extendall` maps `extend` over all placements on  $k$  rows to get all placements on  $k+1$  rows
- ▶ All possible placements of  $n$  queens
  - ▶ `allqueens n = head (drop n (iterate extendall [[]]))`
- ▶ One placement of  $n$  queens
  - ▶ `queens n = head (allqueens n)`

## Queens ...

```
n :: Int
n = ..

extend l = [(x:l) | x <- [1..n], compat x l]

compat x [] = True
compat x l = not (elem x l) && (notdiag x l)

extendall l = concatMap extend l

allqueens = head (drop n (iterate extendall [[]]))
queens = head allqueens
```