

# Introduction to Programming: Lecture 10

K Narayan Kumar

Chennai Mathematical Institute

<http://www.cmi.ac.in/~kumar>

10 Sep 2013

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

3

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

3 5

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

3 5 8

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

3 (5 8 \*)

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

3 40



# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

(3 40 +)

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

2

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

2 3

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

(2 3 +)

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

5



# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

5 7

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

5 7 2

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

5 (7 2 +)

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

5 9

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

(5 9 -)

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

-4

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

-4

# Evaluating postfix expressions

- ▶ Follow the bracketing algorithm, and evaluate each expression as it is created.

3 5 8 \* +

43

- ▶ Another example:

2 3 + 7 2 + -

-4

- ▶ Keep a **stack** of numbers.
  - ▶ If you see a number, **push** it on to the stack.
  - ▶ If you seen an operator, remove the top two elements from the stack, evaluate and push the result on the stack.



# Programming the calculator in Haskell

- ▶ The structure of the program:

# Programming the calculator in Haskell

- ▶ The structure of the program:
  - ▶ A module to manage stacks.

# Programming the calculator in Haskell

- ▶ The structure of the program:
  - ▶ A module to manage stacks.
  - ▶ A module that handles expressions and their evaluation.

# The **Stack** module

- ▶ Methods `empty`, `push`, `pop` and `isempty`.

# The `Stack` module

- ▶ Methods `empty`, `push`, `pop` and `isempty`.
- ▶ As general a type as possible for `Stack`.

# The **Stack** module

- ▶ Methods `empty`, `push`, `pop` and `isempty`.
- ▶ As general a type as possible for `Stack`.

```
data Stack a = Empty | Stack a (Stack a)
empty :: Stack a
empty = Empty
```

```
push :: a -> Stack a -> Stack a
push x st = Stack x st
```

```
pop :: Stack a -> (a, Stack a)
pop (Stack x st) = (x, st)
```

```
isempty :: Stack a -> Bool
isempty Empty = True
isempty _      = False
```

# The **Stack** module

- ▶ Methods `empty`, `push`, `pop` and `isempty`.
- ▶ As general a type as possible for `Stack`.

```
data Stack a = Empty | Stack a (Stack a)
empty :: Stack a
empty = Empty
```

```
push :: a -> Stack a -> Stack a
push x st = Stack x st
```

```
pop :: Stack a -> (a, Stack a)
pop (Stack x st) = (x, st)
```

```
isempty :: Stack a -> Bool
isempty Empty = True
isempty _     = False
```

- ▶ It looks very much like a `list`!

## The `Stack` module via lists

```
data Stack a = Stack [a]

empty :: Stack a
empty = Stack []

push :: a -> Stack a -> Stack a
push x (Stack ls) = Stack (x:ls)

pop :: Stack a -> (a, Stack a)
pop (Stack (x:ls)) = (x, Stack ls)

isempty :: Stack a -> Bool
isempty (Stack []) = True
isempty _           = False
```



# The `Stack` Module

- ▶ The module exports the following

# The `Stack` Module

- ▶ The module exports the following
- ▶ The data type `Stack` without any of its constructors.

# The `Stack` Module

- ▶ The module exports the following
- ▶ The data type `Stack` without any of its constructors.
- ▶ The methods `empty`, `push`, `pop` and `isempty`

# The Stack Module

- ▶ The module exports the following
- ▶ The data type `Stack` without any of its constructors.
- ▶ The methods `empty`, `push`, `pop` and `isempty`  
`module Stack(Stack(),empty,push,pop,isempty) where`  
`data Stack a = ...`

```
empty :: Stack a
```

```
...
```

```
push :: a -> Stack a -> Stack a
```

```
...
```

```
pop :: Stack a -> (a, Stack a)
```

```
...
```

```
isempty :: Stack a -> Bool
```

```
...
```

# The calculator module

- ▶ The postfix expression is a sequence of integers and operators.

# The calculator module

- ▶ The postfix expression is a sequence of integers and operators.
- ▶ How do we represent it in Haskell?

# The calculator module

- ▶ The postfix expression is a sequence of integers and operators.
- ▶ How do we represent it in Haskell?
- ▶ We use the word `Token` to denote an element of the expression

# The calculator module

- ▶ The postfix expression is a sequence of integers and operators.
- ▶ How do we represent it in Haskell?
- ▶ We use the word `Token` to denote an element of the expression

```
data Token = Val Int | Op Char
```



# The calculator module

- ▶ The postfix expression is a sequence of integers and operators.
- ▶ How do we represent it in Haskell?
- ▶ We use the word `Token` to denote an element of the expression

```
data Token = Val Int | Op Char
```

```
type Expr = [Token]
```

# Evaluating an expression

- ▶ An one step evaluation function:

# Evaluating an expression

- ▶ An one step evaluation function:

```
evalStep :: Stack Int -> Token -> Stack Int
```

# Evaluating an expression

- An one step evaluation function:

```
evalStep :: Stack Int -> Token -> Stack Int
```

```
evalStep st (Val i) = push i st
```

```
evalStep st (Op c)
```

```
    | c == '+' = push (v2 + v1) st2
```

```
    | c == '-' = push (v2 - v1) st2
```

```
    | c == '*' = push (v2 * v1) st2
```

```
        where
```

```
            (v1,st1) = pop st
```

```
            (v2,st2) = pop st1
```

# Evaluating an expression

- An one step evaluation function:

```
evalStep :: Stack Int -> Token -> Stack Int
```

```
evalStep st (Val i) = push i st
```

```
evalStep st (Op c)
```

```
    | c == '+' = push (v2 + v1) st2
```

```
    | c == '-' = push (v2 - v1) st2
```

```
    | c == '*' = push (v2 * v1) st2
```

```
        where
```

```
            (v1,st1) = pop st
```

```
            (v2,st2) = pop st1
```

- How to iterate this and evaluate the entire expression?

# Evaluating an expression

# Evaluating an expression

- ▶ The top of stack has the answer at the end.

# Evaluating an expression

- ▶ The top of stack has the answer at the end.

```
evalExp st [] = fst (pop st)
```



# Evaluating an expression

- ▶ The top of stack has the answer at the end.

```
evalExp st [] = fst (pop st)
```

- ▶ Otherwise, evaluate recursively using `evalStep`

# Evaluating an expression

- ▶ The top of stack has the answer at the end.

```
evalExp st [] = fst (pop st)
```

- ▶ Otherwise, evaluate recursively using `evalStep`

```
evalExp st (e:es) = evalExp (evalStep st e) es
```

# Evaluating an expression

- ▶ The top of stack has the answer at the end.

```
evalExp st [] = fst (pop st)
```

- ▶ Otherwise, evaluate recursively using `evalStep`

```
evalExp st (e:es) = evalExp (evalStep st e) es
```

```
evaluate exp = evalExp empty exp
```

# Evaluating an expression

- ▶ The top of stack has the answer at the end.

```
evalExp st [] = fst (pop st)
```

- ▶ Otherwise, evaluate recursively using `evalStep`

```
evalExp st (e:es) = evalExp (evalStep st e) es
```

```
evaluate exp = evalExp empty exp
```

- ▶ Now, we can use any implementation of the `Stack` and it works identically.

# Queues

- ▶ Queues follow the First-in first-out rule.

# Queues

- ▶ Queues follow the First-in first-out rule.
- ▶ Required operations

# Queues

- ▶ Queues follow the First-in first-out rule.
- ▶ Required operations

```
emptyq :: Queue a  
addq  :: a -> (Queue a) -> (Queue a)  
removeq :: (Queue a) -> (a, Queue a)  
isemptyq :: (Queue a) -> Bool
```

# Queues

- ▶ Queues follow the First-in first-out rule.
- ▶ Required operations

```
emptyq :: Queue a  
addq  :: a -> (Queue a) -> (Queue a)  
removeq :: (Queue a) -> (a, Queue a)  
isemptyq :: (Queue a) -> Bool
```

- ▶ Again, represent a queue using a list

```
data Queue a = Qu [a]  
  
emptyq = Qu []  
addq x (Qu xs) = (Qu (xs ++ [x]))  
removeq (Qu (x:xs)) = (x, Qu xs)  
isempty (Qu l) = (l == [])
```



## Queues ...

- ▶ Inserting takes  $O(n)$  time!

# Queues ...

- ▶ Inserting takes  $O(n)$  time!
- ▶ If we reverse the representation?

```
addq x (Qu xs) = (Qu (x:xs))
```

```
removeq (Qu xs) = ((last x), Qu (init xs))
```

# Queues ...

- ▶ Inserting takes  $O(n)$  time!
- ▶ If we reverse the representation?

```
addq x (Qu xs) = (Qu (x:xs))
```

```
removeq (Qu xs) = ((last xs), Qu (init xs))
```

Now, removing an element takes  $O(n)$  time.

Adding and removing  $n$  elements could take  $O(n^2)$  time

# Queues with two lists

# Queues with two lists

- ▶ Use two lists

# Queues with two lists

- ▶ Use two lists
- ▶ Split queue and store the rear in reversed order in a **reversed**

Represent  $[q_1, q_2, \dots, q_n]$

as  $[q_1, q_2, \dots, q_i], [q_n, q_{n-1}, \dots, q_{i+1}]$

# Queues with two lists

- ▶ Use two lists
- ▶ Split queue and store the rear in reversed order in a **reversed**

Represent  $[q_1, q_2, \dots, q_n]$

as  $[q_1, q_2, \dots, q_i], [q_n, q_{n-1}, \dots, q_{i+1}]$

- ▶ **addq** adds an element at beginning of second list in time  $O(1)$

# Queues with two lists

- ▶ Use two lists
- ▶ Split queue and store the rear in reversed order in a **reversed**

Represent  $[q_1, q_2, \dots, q_n]$

as  $[q_1, q_2, \dots, q_i], [q_n, q_{n-1}, \dots, q_{i+1}]$

- ▶ **addq** adds an element at beginning of second list in time  $O(1)$
- ▶ **removeq** removes the element at the beginning of first list in time  $O(1)$ , if this list is nonempty!



# Queues with two lists

- ▶ Use two lists
- ▶ Split queue and store the rear in reversed order in a **reversed**

Represent  $[q_1, q_2, \dots, q_n]$   
as  $[q_1, q_2, \dots, q_i], [q_n, q_{n-1}, \dots, q_{i+1}]$

- ▶ **addq** adds an element at beginning of second list in time  $O(1)$
- ▶ **removeq** removes the element at the beginning of first list in time  $O(1)$ , if this list is nonempty!
- ▶ What happens if the first list is empty?

# Queues with two lists

- ▶ Use two lists
- ▶ Split queue and store the rear in reversed order in a **reversed**

Represent  $[q_1, q_2, \dots, q_n]$

as  $[q_1, q_2, \dots, q_i], [q_n, q_{n-1}, \dots, q_{i+1}]$

- ▶ **addq** adds an element at beginning of second list in time  $O(1)$
- ▶ **removeq** removes the element at the beginning of first list in time  $O(1)$ , if this list is nonempty!
- ▶ What happens if the first list is empty?
- ▶ If the first list is empty, reverse the second list on to the first list and then remove the first element.

## Queues ...

```
data Queue a = Nuqu [a] [a]
```

# Queues ...

```
data Queue a = Nuqu [a] [a]
```

- ▶ Definition of queue functions
- ▶ `addq` adds to second list

```
addq x (Nuqu ys zs) = Nuqu ys (x:zs)
```

# Queues ...

```
data Queue a = Nuqu [a] [a]
```

- Definition of queue functions

- `addq` adds to second list

```
addq x (Nuqu ys zs) = Nuqu ys (x:zs)
```

- `removeq` takes from first list, reversing elements from second list into first list if necessary

```
removeq (Nuqu (x:xs) ys) = (x,Nuqu xs ys)
```

```
removeq (Nuqu [] ys) = removeq (Nuqu (reverse ys) [])
```

# Queues ...

```
data Queue a = Nuqu [a] [a]
```

- Definition of queue functions

- `addq` adds to second list

```
addq x (Nuqu ys zs) = Nuqu ys (x:zs)
```

- `removeq` takes from first list, reversing elements from second list into first list if necessary

```
removeq (Nuqu (x:xs) ys) = (x,Nuqu xs ys)  
removeq (Nuqu [] ys)    = removeq (Nuqu (reverse ys) [])
```

- If we add  $n$  elements, we get a queue `Nuqu [] [qn,...,q1]`

# Queues ...

```
data Queue a = Nuqu [a] [a]
```

- ▶ Definition of queue functions

- ▶ `addq` adds to second list

```
addq x (Nuqu ys zs) = Nuqu ys (x:zs)
```

- ▶ `removeq` takes from first list, reversing elements from second list into first list if necessary

```
removeq (Nuqu (x:xs) ys) = (x, Nuqu xs ys)  
removeq (Nuqu [] ys)    = removeq (Nuqu (reverse ys) [])
```

- ▶ If we add  $n$  elements, we get a queue `Nuqu [] [qn, ..., q1]`
  - ▶ Next `removeq` takes  $O(n)$  time to reverse the second list

# Queues ...

```
data Queue a = Nuqu [a] [a]
```

- ▶ Definition of queue functions

- ▶ `addq` adds to second list

```
addq x (Nuqu ys zs) = Nuqu ys (x:zs)
```

- ▶ `removeq` takes from first list, reversing elements from second list into first list if necessary

```
removeq (Nuqu (x:xs) ys) = (x,Nuqu xs ys)
```

```
removeq (Nuqu [] ys) = removeq (Nuqu (reverse ys) [])
```

- ▶ If we add  $n$  elements, we get a queue `Nuqu [] [qn,...,q1]`
  - ▶ Next `removeq` takes  $O(n)$  time to reverse the second list
  - ▶ After one `removeq`, we have `Nuqu [q2,...,qn] []`
  - ▶ Next  $n - 1$  `removeq` operations take time  $O(1)$ !



# Amortised analysis

- ▶ How many times is an element **touched**.

# Amortised analysis

- ▶ How many times is an element **touched**.
  - ▶ Once when it is inserted (into the second list)

# Amortised analysis

- ▶ How many times is an element **touched**.
  - ▶ Once when it is inserted (into the second list)
  - ▶ Twice when it moves from the second list to the first list.

# Amortised analysis

- ▶ How many times is an element **touched**.
  - ▶ Once when it is inserted (into the second list)
  - ▶ Twice when it moves from the second list to the first list.
  - ▶ Once when it is removed (from the first list)

# Amortised analysis

- ▶ How many times is an element **touched**.
  - ▶ Once when it is inserted (into the second list)
  - ▶ Twice when it moves from the second list to the first list.
  - ▶ Once when it is removed (from the first list)
- ▶ Each element can be touched only four times.

# Amortised analysis

- ▶ How many times is an element **touched**.
  - ▶ Once when it is inserted (into the second list)
  - ▶ Twice when it moves from the second list to the first list.
  - ▶ Once when it is removed (from the first list)
- ▶ Each element can be touched only four times.
- ▶ In any sequence of  $N$  instructions at most  $N$  elements are involved.

# Amortised analysis

- ▶ How many times is an element **touched**.
  - ▶ Once when it is inserted (into the second list)
  - ▶ Twice when it moves from the second list to the first list.
  - ▶ Once when it is removed (from the first list)
- ▶ Each element can be touched only four times.
- ▶ In any sequence of  $N$  instructions at most  $N$  elements are involved.
- ▶ Any sequence of  $N$  instructions can take only  $O(N)$  steps!

# The Set datastructure

- ▶ Maintain a collection of distinct elements and support the following operations



# The Set datastructure

- ▶ Maintain a collection of distinct elements and support the following operations
  - ▶ `insert` : inserts a given value into the set.

# The Set datastructure

- ▶ Maintain a collection of distinct elements and support the following operations
  - ▶ `insert` : inserts a given value into the set.
  - ▶ `delete` : deletes a given value from the set.

# The Set datastructure

- ▶ Maintain a collection of distinct elements and support the following operations
  - ▶ `insert` : inserts a given value into the set.
  - ▶ `delete` : deletes a given value from the set.
  - ▶ `search` : checks whether a given value is an element of the set.

# The `Set` datastructure

- ▶ Maintain a collection of distinct elements and support the following operations
  - ▶ `insert` : inserts a given value into the set.
  - ▶ `delete` : deletes a given value from the set.
  - ▶ `search` : checks whether a given value is an element of the set.

```
data Eq a => Set a = Set [a]
```

# The Set datastructure

- ▶ Maintain a collection of distinct elements and support the following operations
  - ▶ `insert` : inserts a given value into the set.
  - ▶ `delete` : deletes a given value from the set.
  - ▶ `search` : checks whether a given value is an element of the set.

```
data Eq a => Set a = Set [a]  
search x (Set y)= elem x y
```

# The Set datastructure

- ▶ Maintain a collection of distinct elements and support the following operations
  - ▶ `insert` : inserts a given value into the set.
  - ▶ `delete` : deletes a given value from the set.
  - ▶ `search` : checks whether a given value is an element of the set.

```
data Eq a => Set a = Set [a]
search x (Set y)= elem x y
insert x (Set s)
  | elem x (Set s)  = Set s
  | otherwise      = Set (x:s)
```

# The `Set` datastructure

- ▶ Maintain a collection of distinct elements and support the following operations
  - ▶ `insert` : inserts a given value into the set.
  - ▶ `delete` : deletes a given value from the set.
  - ▶ `search` : checks whether a given value is an element of the set.

```
data Eq a => Set a = Set [a]
search x (Set y)= elem x y
insert x (Set s)
  | elem x (Set s)  = Set s
  | otherwise      = Set (x:s)
delete x (Set s)   = Set (filter (/= x) s)
```

# Complexity of the operations



# Complexity of the operations

- ▶ `search` takes linear time.

# Complexity of the operations

- ▶ `search` takes linear time.
- ▶ `insert` takes linear time.

# Complexity of the operations

- ▶ `search` takes linear time.
- ▶ `insert` takes linear time.
- ▶ `delete` takes linear time.

# Complexity of the operations


- ▶ `search` takes linear time.
- ▶ `insert` takes linear time.
- ▶ `delete` takes linear time.
- ▶ A sequence of  $N$  operations can take  $O(N^2)$  time.

# Complexity of the operations

- ▶ `search` takes linear time.
- ▶ `insert` takes linear time.
- ▶ `delete` takes linear time.
- ▶ A sequence of  $N$  operations can take  $O(N^2)$  time.
- ▶ We can do better if the elements of the type `a` can be ordered.

# A datatype for binary trees

- ▶ Trees are **recursive** datatypes
- ▶ A tree is either
  - ▶ Empty
  - ▶ Or is a node containing a value and two trees



# The binary tree datatype

# The binary tree datatype

```
data Btree a = Nil | Node (Btree a) a (Btree a)
```



# The binary tree datatype

```
data Btree a = Nil | Node (Btree a) a (Btree a)
```

- ▶ `Nil` and `Node` are the constructors.

# The binary tree datatype

```
data Btree a = Nil | Node (Btree a) a (Btree a)
```

- ▶ `Nil` and `Node` are the constructors.
- ▶ `Nil` represents the empty tree.

# The binary tree datatype

```
data Btree a = Nil | Node (Btree a) a (Btree a)
```

- ▶ `Nil` and `Node` are the constructors.
- ▶ `Nil` represents the empty tree.
- ▶ A nonempty tree (identified by the constructor `Node`) has three parts
  - ▶ A left (sub-)tree
  - ▶ A value
  - ▶ A right (sub-)tree

# Examples of trees

```
Node (Node Nil 2 Nil) 3 (Node Nil 5 Nil)
```

# Examples of trees

```
Node (Node Nil 2 Nil) 3 (Node Nil 5 Nil)
```



# Examples of trees

```
Node (Node Nil 2 Nil) 3 (Node Nil 5 Nil)
```



```
Node (Node Nil 4 Nil) 6  
      (Node (Node Nil 2 Nil) 3 (Node Nil 5 Nil))
```

# Examples of trees

```
Node (Node Nil 2 Nil) 3 (Node Nil 5 Nil)
```



```
Node (Node Nil 4 Nil) 6  
  (Node (Node Nil 2 Nil) 3 (Node Nil 5 Nil))
```



# Binary Trees ...

- What about





# Binary Trees ...

- What about



```
Node (Node (Node Nil 1 Nil) 2 (Node Nil 3 Nil))  
4 (Node Nil 5 Nil)
```

# Functions on Binary trees

- ▶ `size` – Number of nodes in the tree

# Functions on Binary trees

- `size` – Number of nodes in the tree

```
size :: Btree a -> Int
```

```
size Nil = 0
```

```
size (Node tl x tr) = 1 + (size tl) + (size tr)
```

# Functions on Binary trees

- ▶ `size` – Number of nodes in the tree

```
size :: Btree a -> Int
size Nil = 0
size (Node tl x tr) = 1 + (size tl) + (size tr)
```

- ▶ `height` – Longest path from the root to a leaf

# Functions on Binary trees

- `size` – Number of nodes in the tree

```
size :: Btree a -> Int
size Nil = 0
size (Node t1 x tr) = 1 + (size t1) + (size tr)
```

- `height` – Longest path from the root to a leaf

```
height :: Btree a -> Int
height Nil = 0
height (Node t1 x tr) =
    1 + (max (height t1) (height tr))
```

# Levels

- List nodes level by level and from left to right within each level.



# Levels

- List nodes level by level and from left to right within each level.



[4,2,5,1,3]