

Introduction to Programming: Lecture 18

K Narayan Kumar

Chennai Mathematical Institute

<http://www.cmi.ac.in/~kumar>

17 Oct 2013

Compiling into executables

- ▶ So far,
 - ▶ All inputs were supplied as arguments to functions from `ghci`
 - ▶ Outputs were printed out by `ghci`

Compiling into executables

- ▶ So far,
 - ▶ All inputs were supplied as arguments to functions from `ghci`
 - ▶ Outputs were printed out by `ghci`
- ▶ Works as long as programs are run from within an interpreter.

Compiling into executables

- ▶ So far,
 - ▶ All inputs were supplied as arguments to functions from `ghci`
 - ▶ Outputs were printed out by `ghci`
- ▶ Works as long as programs are run from within an interpreter.
- ▶ What if we want to **compile** programs into executables?

Compiling into executables

- ▶ So far,
 - ▶ All inputs were supplied as arguments to functions from `ghci`
 - ▶ Outputs were printed out by `ghci`
- ▶ Works as long as programs are run from within an interpreter.
- ▶ What if we want to **compile** programs into executables?
- ▶ The Haskell programs described so far cannot be compiled into executables.

Compiling into executables

- ▶ So far,
 - ▶ All inputs were supplied as arguments to functions from `ghci`
 - ▶ Outputs were printed out by `ghci`
- ▶ Works as long as programs are run from within an interpreter.
- ▶ What if we want to **compile** programs into executables?
- ▶ The Haskell programs described so far cannot be compiled into executables.
 - ▶ For eg. they don't specify what function has to be computed.

Compiling ...

- ▶ Consider the Haskell program

```
main = putStrLn ("My First Compilable Program")
```

Compiling ...

- ▶ Consider the Haskell program

```
main = putStrLn ("My First Compilable Program")
```

- ▶ Compile the program using `ghc`

```
ghc -make Out.hs
```


Compiling ...

- ▶ Consider the Haskell program

```
main = putStrLn ("My First Compilable Program")
```

- ▶ Compile the program using `ghc`

```
ghc -make Out.hs
```

- ▶ Computes all the module dependencies and compiles all the modules.

Compiling ...

- ▶ Consider the Haskell program

```
main = putStrLn ("My First Compilable Program")
```

- ▶ Compile the program using `ghc`

```
ghc -make Out.hs
```

- ▶ Computes all the module dependencies and compiles all the modules.
- ▶ Run by executing the program `Out`

Compiling ...

- ▶ Consider the Haskell program

```
main = putStrLn ("My First Compilable Program")
```

- ▶ Compile the program using `ghc`

```
ghc -make Out.hs
```

- ▶ Computes all the module dependencies and compiles all the modules.
- ▶ Run by executing the program `Out`
- ▶ How do we give inputs to a Haskell program that is compiled and executed?

Input/Output in Haskell

- ▶ Here is a simple program that does both input and output.

```
main = do
    putStrLn ("Please enter your name:")
    name <- getLine
    putStrLn ("Hello " ++ name)
```

Input/Output in Haskell

- ▶ Here is a simple program that does both input and output.

```
main = do
    putStrLn ("Please enter your name:")
    name <- getLine
    putStrLn ("Hello " ++ name)
```

- ▶ `main` is the name of the **action** that is executed when a compiled Haskell program is run.

Input/Output in Haskell

- ▶ Here is a simple program that does both input and output.

```
main = do
    putStrLn ("Please enter your name:")
    name <- getLine
    putStrLn ("Hello " ++ name)
```

- ▶ `main` is the name of the **action** that is executed when a compiled Haskell program is run.
- ▶ `main`, `putStrLn s`, `getLine` are all **actions**.

Input/Output in Haskell

- ▶ Here is a simple program that does both input and output.

```
main = do
    putStrLn ("Please enter your name:")
    name <- getLine
    putStrLn ("Hello " ++ name)
```

- ▶ `main` is the name of the **action** that is executed when a compiled Haskell program is run.
- ▶ `main`, `putStrLn s`, `getLine` are all **actions**.
- ▶ The `do` command puts together a sequence of **actions** into a larger **action**.

Input/Output in Haskell

- ▶ Here is a simple program that does both input and output.

```
main = do
    putStrLn ("Please enter your name:")
    name <- getLine
    putStrLn ("Hello " ++ name)
```

- ▶ `main` is the name of the **action** that is executed when a compiled Haskell program is run.
- ▶ `main`, `putStrLn s`, `getLine` are all **actions**.
- ▶ The `do` command puts together a sequence of **actions** into a larger **action**.
- ▶ These actions are executed **sequentially**, that is, one after the other.

The type of Actions

- ▶ What is the type of `main` in this example?

The type of Actions

- ▶ What is the type of `main` in this example?

```
main : IO ()
```

The type of Actions

- ▶ What is the type of `main` in this example?

```
main : IO ()
```

- ▶ The type `()` is the type with a single value, also denoted `()`.

The type of Actions

- ▶ What is the type of `main` in this example?

```
main : IO ()
```

- ▶ The type `()` is the type with a single value, also denoted `()`.
- ▶ What are the types of `putStrLn` and `getLine` ?

The type of Actions

- ▶ What is the type of `main` in this example?

```
main : IO ()
```

- ▶ The type `()` is the type with a single value, also denoted `()`.
- ▶ What are the types of `putStrLn` and `getLine` ?

```
putStrLn :: String -> IO ()
```

```
getLine  :: IO String
```

The type of Actions

- ▶ What is the type of `main` in this example?

```
main : IO ()
```

- ▶ The type `()` is the type with a single value, also denoted `()`.
- ▶ What are the types of `putStrLn` and `getLine` ?

```
putStrLn :: String -> IO ()
```

```
getLine :: IO String
```

- ▶ The **qualifier** `IO` in all these types indicate that the function also performs some Input/Output.

The type of Actions

- ▶ What is the type of `main` in this example?

```
main : IO ()
```

- ▶ The type `()` is the type with a single value, also denoted `()`.
- ▶ What are the types of `putStrLn` and `getLine` ?

```
putStrLn :: String -> IO ()
```

```
getLine :: IO String
```

- ▶ The **qualifier** `IO` in all these types indicate that the function also performs some Input/Output.
- ▶ The type of a `do ..` statement is the type of the last action.
The type of an action `v <- e` is the type of `e`.

Actions

- ▶ An **action** is an expression of type `IO a` for some `a`.
`main`, `putStrLn s` and `getLine` are all actions.

Actions

- ▶ An **action** is an expression of type `IO a` for some `a`.
`main`, `putStrLn s` and `getLine` are all actions.
- ▶ In Haskell, any Input/Output must occur within expressions of type `IO a` for some `a`.

Actions

- ▶ An **action** is an expression of type `IO a` for some `a`.
`main`, `putStrLn s` and `getLine` are all actions.
- ▶ In Haskell, any Input/Output must occur within expressions of type `IO a` for some `a`.
- ▶ Actions are first class values and for most part can be used like other normal values.

```
alist = map putStrLn ["one","two","three"]  
c = head alist
```

Actions

- ▶ An **action** is an expression of type `IO a` for some `a`.
`main`, `putStrLn s` and `getLine` are all actions.
- ▶ In Haskell, any Input/Output must occur within expressions of type `IO a` for some `a`.

- ▶ Actions are first class values and for most part can be used like other normal values.

```
alist = map putStrLn ["one","two","three"]  
c = head alist
```

- ▶ As expected, we have

```
alist :: [IO ()]
```

Actions

- ▶ An **action** is an expression of type `IO a` for some `a`.
`main`, `putStrLn s` and `getLine` are all actions.
- ▶ In Haskell, any Input/Output must occur within expressions of type `IO a` for some `a`.
- ▶ Actions are first class values and for most part can be used like other normal values.

```
alist = map putStrLn ["one","two","three"]  
c = head alist
```

- ▶ As expected, we have

```
alist :: [IO ()]  
c :: IO ()
```

I/O ...

- ▶ A function with an integer for an argument and returning an integer has type

`Int -> Int`

while one that also does some IO has type

`(Int -> IO Int)`

I/O ...

- ▶ A function with an integer for an argument and returning an integer has type

`Int -> Int`

while one that also does some IO has type

`(Int -> IO Int)`

What is the need for such a distinction?

I/O ...

- ▶ A function with an integer for an argument and returning an integer has type

`Int -> Int`

while one that also does some IO has type

`(Int -> IO Int)`

What is the need for such a distinction?

- ▶ The kind of Haskell functions we have so far seen in this course are called **pure** functions.

I/O ...

- ▶ A function with an integer for an argument and returning an integer has type

`Int -> Int`

while one that also does some IO has type

`(Int -> IO Int)`

What is the need for such a distinction?

- ▶ The kind of Haskell functions we have so far seen in this course are called **pure** functions.
Their type gives all the information we need about them.

I/O ...

- ▶ A function with an integer for an argument and returning an integer has type

`Int -> Int`

while one that also does some IO has type

`(Int -> IO Int)`

What is the need for such a distinction?

- ▶ The kind of Haskell functions we have so far seen in this course are called **pure** functions.
Their type gives all the information we need about them.
- ▶ For functions that also do IO, the types of the arguments and the return value by themselves do not reveal everything.

I/O ...

- ▶ A function with an integer for an argument and returning an integer has type

`Int -> Int`

while one that also does some IO has type

`(Int -> IO Int)`

What is the need for such a distinction?

- ▶ The kind of Haskell functions we have so far seen in this course are called **pure** functions.
Their type gives all the information we need about them.
- ▶ For functions that also do IO, the types of the arguments and the return value by themselves do not reveal everything.
 - ▶ Input/Output involves changing the **outside** world.
state change
 - ▶ I/O Actions have to be composed **sequentially**, that is, the order of execution is critical.

- ▶ A function with an integer for an argument and returning an integer has type

`Int -> Int`

while one that also does some IO has type

`(Int -> IO Int)`

What is the need for such a distinction?

- ▶ The kind of Haskell functions we have so far seen in this course are called **pure** functions.
Their type gives all the information we need about them.
- ▶ For functions that also do IO, the types of the arguments and the return value by themselves do not reveal everything.
 - ▶ Input/Output involves changing the **outside** world.
state change
 - ▶ I/O Actions have to be composed **sequentially**, that is, the order of execution is critical.
(eg.) Reading in different orders will result in different behaviours.

Combining Pure and IO functions

- ▶ Haskell type system allows us use pure and **action** parts in a **safe** manner.

Combining Pure and IO functions

- ▶ Haskell type system allows us use pure and **action** parts in a **safe** manner.
- ▶ There is no mechanism to execute an action from within a pure function.

Combining Pure and IO functions

- ▶ Haskell type system allows us use pure and **action** parts in a **safe** manner.
- ▶ There is no mechanism to execute an action from within a pure function.
- ▶ I/O is **performed** by an action only if it that action is **performed**, i.e. executed from within another action.

Combining Pure and IO functions

- ▶ Haskell type system allows us use pure and **action** parts in a **safe** manner.
- ▶ There is no mechanism to execute an action from within a pure function.
- ▶ I/O is **performed** by an action only if it that action is **performed**, i.e. executed from within another action.

The **main** action is where all the **action** begins!

I/O Examples ...

- ▶ Read a line and print it out twice

I/O Examples ...

- ▶ Read a line and print it out twice

```
main = do
    inp <- getLine
    putStrLn inp;
    putStrLn inp;
```

I/O Examples ...

- ▶ Read a line and print it out twice

```
main = do
    inp <- getLine
    putStrLn inp;
    putStrLn inp;
```

- ▶ Read a line and print it out as many times as its length

I/O Examples ...

- Read a line and print it out twice

```
main = do
    inp <- getLine
    putStrLn inp;
    putStrLn inp;
```

- Read a line and print it out as many times as its length

```
main = do
    inp <- getLine
    ltimes (length inp) inp
```

```
ltimes :: Int -> String -> IO ()
ltimes 1 l = putStrLn l
ltimes n l = do
    putStrLn l
    ltimes (n-1) l
```

Example ...

- ▶ Read a line `w`. Read and output as many lines as length of `w`.

Example ...

- Read a line `w`. Read and output as many lines as length of `w`.

```
main = do
    linp <- getLine
    ltimesrw (length linp)

ltimesrw :: Int -> IO ()
ltimesrw 1 = do
    inp <- getLine
    putStrLn inp
ltimesrw n = do
    inp <- getLine
    putStrLn inp
    ltimesrw (n-1)
```

Example ...

- Read a line `w`. Read and output as many lines as length of `w`.

```
main = do
    linp <- getLine
    ltimesrw (length linp)
```

```
ltimesrw :: Int -> IO ()
ltimesrw 1 = do
    inp <- getLine
    putStrLn inp
ltimesrw n = do
    inp <- getLine
    putStrLn inp
    ltimesrw (n-1)
```

- Suggests that we should write a function to do an action `n` times.

ntimes

- Repeat an action *n* times.

```
ntimes :: Int -> IO () -> IO ()
```

```
ntimes 1 s = s
```

```
ntimes n s = do
```

```
    s
```

```
    ntimes (n-1) s
```

ntimes

- Repeat an action n times.

```
ntimes :: Int -> IO () -> IO ()  
ntimes 1 s = s  
ntimes n s = do  
    s  
    ntimes (n-1) s
```

- Then we can write

```
action1 = do  
    inp <- getLine  
    ntimes (length inp)  
        (putStrLn inp)
```


ntimes

- Repeat an action n times.

```
ntimes :: Int -> IO () -> IO ()
ntimes 1 s = s
ntimes n s = do
    s
    ntimes (n-1) s
```

- Then we can write

```
action1 = do
    inp <- getLine
    ntimes (length inp)
    (putStrLn inp)
```

- and

```
action2 = do
    linp <- getLine
    ntimes (length linp)
    (do
        inp <- getLine
        putStrLn inp)
```

Reading other types

- ▶ The function `readLn` reads a value of any type `a` that is an instance of `Read a`

```
readLn :: (Read a) => IO a
```

Reading other types

- ▶ The function `readLn` reads a value of any type `a` that is an instance of `Read a`

```
readLn :: (Read a) => IO a
```

- ▶ All basic types (`Int`, `Float`, `Bool`, ...) are instances of `Read`.

Reading other types

- ▶ The function `readLn` reads a value of any type `a` that is an instance of `Read a`

```
readLn :: (Read a) => IO a
```

- ▶ All basic types (`Int`, `Float`, `Bool`, ...) are instances of `Read`.

```
main = do
    inp <- (readLn :: IO Bool)
    putStrLn (show inp)
```

Reading other types

- ▶ The function `readLn` reads a value of any type `a` that is an instance of `Read a`

```
readLn :: (Read a) => IO a
```

- ▶ All basic types (`Int`, `Float`, `Bool`, ...) are instances of `Read`.

```
main = do
    inp <- (readLn :: IO Bool)
    putStrLn (show inp)
```

- ▶ `readLn` reads a value of the appropriate type appearing by itself in a line.

Reading other types

- ▶ The function `readLn` reads a value of any type `a` that is an instance of `Read a`

```
readLn :: (Read a) => IO a
```

- ▶ All basic types (`Int`, `Float`, `Bool`, ...) are instances of `Read`.

```
main = do
    inp <- (readLn :: IO Bool)
    putStrLn (show inp)
```

- ▶ `readLn` reads a value of the appropriate type appearing by itself in a line.

```
main = do
    inp <- (readLn :: IO Float)
    putStrLn (show (inp*inp))
```

IO Examples

- ▶ Read a list of positive integers, terminated by a `-1`, into a `list` and print the sum.

IO Examples

- ▶ Read a list of positive integers, terminated by a `-1`, into a `list` and print the sum.

```
main = do
    ls <- (readlist [])
    putStrLn (sum ls)
```


IO Examples

- Read a list of positive integers, terminated by a `-1`, into a `list` and print the sum.

```
main = do
    ls <- (readlist [])
    putStrLn (sum ls)

readlist :: [Int] -> IO [Int]
readlist l = do
    inp <- (readLn :: IO Int)
    if (inp == -1)
    then l
    else readlist (inp:l)
```

IO Examples

- ▶ Read a list of positive integers, terminated by a `-1`, into a `list` and print the sum.

```
main = do
    ls <- (readlist [])
    putStrLn (sum ls)

readlist :: [Int] -> IO [Int]
readlist l = do
    inp <- (readLn :: IO Int)
    if (inp == -1)
    then l
    else readlist (inp:l)
```

- ▶ This is not typed correctly. `l` has type `[Int]` and not `IO [Int]`.

Example ...

```
readlist :: [Int] -> IO [Int]
readlist l = do
    inp <- (readLn :: IO Int)
    if (inp == -1)
    then (return l)
    else readlist (inp:l)
```

Example ...

```
readlist :: [Int] -> IO [Int]
readlist l = do
    inp <- (readLn :: IO Int)
    if (inp == -1)
    then (return l)
    else readlist (inp:l)
```

- The function `return` sends value of type `a` to a value of type `IO a`

Example ...

```
readlist :: [Int] -> IO [Int]
readlist l = do
    inp <- (readLn :: IO Int)
    if (inp == -1)
    then (return l)
    else readlist (inp:l)
```

- ▶ The function `return` sends value of type `a` to a value of type `IO a`
- ▶ Note that there is no obvious way to construct a **useful** function of type `IO a -> b` where `b` is not an action.

Example ...

```
readlist :: [Int] -> IO [Int]
readlist l = do
    inp <- (readLn :: IO Int)
    if (inp == -1)
    then (return l)
    else readlist (inp:l)
```

- ▶ The function `return` sends value of type `a` to a value of type `IO a`
- ▶ Note that there is no obvious way to construct a `useful` function of type `IO a -> b` where `b` is not an action.

This is towards a clean separation of the `pure` fragments of the program (that do no I/O) and the `IO` parts.