

Introduction to Programming: Lecture 1

K Narayan Kumar

Chennai Mathematical Institute
<http://www.cmi.ac.in/~kumar>

06 Aug 2013

About this course ...

About this course ...

- ▶ Learn programming

About this course ...

- ▶ Learn programming in Haskell

About this course ...

- ▶ Learn programming in Haskell
- ▶ Learn to think algorithmically.

About this course ...

- ▶ Learn programming in Haskell
- ▶ Learn to think algorithmically.

Evaluation

About this course ...

- ▶ Learn programming in Haskell
- ▶ Learn to think algorithmically.

Evaluation

- ▶ About 50% weightage to assignments.
- ▶ About 50% weightage to exams.

References

References

- ▶ Lecture notes written for this course by Madhavan Mukund.
(Available at
<http://www.cmi.ac.in/~madhavan/courses/programming08>)

References

- ▶ Lecture notes written for this course by Madhavan Mukund.
(Available at <http://www.cmi.ac.in/~madhavan/courses/programming08>)
- ▶ Online archive at <http://www.haskell.org>
- ▶ Online book at <http://learnyouahaskell.com>

References

- ▶ Lecture notes written for this course by Madhavan Mukund.
(Available at <http://www.cmi.ac.in/~madhavan/courses/programming08>)
- ▶ Online archive at <http://www.haskell.org>
- ▶ Online book at <http://learnyouahaskell.com>
- ▶ **Introduction to Functional Programming** using Haskell by Richard Bird.
- ▶ **A Gentle Introduction to Haskell** by Paul Hudak et al.
- ▶ **Real-world Haskell** by Bryan O'Sullivan, John Goerzen and Don Stewart.

Programs as functions

Functions transform inputs to outputs:



Programs as functions

Functions transform inputs to outputs:



A typical program consists of **rules** to produce an output from an input

Programs as functions

Functions transform inputs to outputs:



A typical program consists of **rules** to produce an output from an input

Computation is the process of applying the rules described by a program

Building up programs

How do we describe the rules?

Building up programs

How do we describe the rules?

- ▶ Start with basic “built in” functions

Building up programs

How do we describe the rules?

- ▶ Start with basic “built in” functions
- ▶ Use these to build more complex functions

Building up programs ...

Suppose

Building up programs ...

Suppose

- ▶ ... there were the whole numbers, $\{0, 1, 2, \dots\}$

Building up programs ...

Suppose

- ▶ ... there were the whole numbers, $\{0, 1, 2, \dots\}$
- ▶ ... and one function, `succ` (successor)

`succ 0 = 1`

`succ 1 = 2`

`succ 2 = 3`

...

Building up programs ...

Suppose

- ▶ ... there were the whole numbers, $\{0, 1, 2, \dots\}$
- ▶ ... and one function, `succ` (successor)

`succ 0 = 1`

`succ 1 = 2`

`succ 2 = 3`

...

Then, we may define `plusTwo`, as

`plusTwo n = succ (succ n)`

by **composing** two copies of `succ`.

Building up programs ...

Suppose

- ▶ ... there were the whole numbers, $\{0, 1, 2, \dots\}$
- ▶ ... and one function, `succ` (successor)

`succ 0 = 1`

`succ 1 = 2`

`succ 2 = 3`

...

Then, we may define `plusTwo`, as

`plusTwo n = succ (succ n)`

by **composing** two copies of `succ`.

Composing `plusTwo` and `succ` we get

`plusThree n = succ (plusTwo n)`

Addition....

- ▶ `plus n m` means apply `succ` to `n m` times

Addition....

- ▶ `plus n m` means apply `succ` to `n m` times

$$\text{plus } n \ m = \underbrace{\text{succ}(\text{succ}(\dots(\text{succ } n)\dots))}_{m \text{ times}}$$

Addition....

- ▶ `plus n m` means apply `succ` to `n m` times

$$\text{plus } n \ m = \underbrace{\text{succ}(\text{succ}(\dots(\text{succ } n)\dots))}_{m \text{ times}}$$

- ▶ How do we describe this rule concisely for all `n` and `m`?

Recursive definitions

Goal: Define `plus n 0`, `plus n 1`, ..., `plus n i`, ... for each `i`

Recursive definitions

Goal: Define `plus n 0`, `plus n 1`, ..., `plus n i`, ... for each `i`

- ▶ `plus n 0 = n`, for every `n`

Recursive definitions

Goal: Define `plus n 0`, `plus n 1`, ..., `plus n i`, ... for each `i`

- ▶ `plus n 0 = n`, for every `n`
- ▶ `plus n 1 = succ n = succ (plus n 0)` , for every `n`

Recursive definitions

Goal: Define `plus n 0`, `plus n 1`, ..., `plus n i`, ... for each `i`

- ▶ `plus n 0 = n`, for every `n`
- ▶ `plus n 1 = succ n = succ (plus n 0)` , for every `n`
- ▶ Suppose we know how to compute `plus n m`

Recursive definitions

Goal: Define `plus n 0`, `plus n 1`, ..., `plus n i`, ... for each `i`

- ▶ `plus n 0 = n`, for every `n`
- ▶ `plus n 1 = succ n = succ (plus n 0)` , for every `n`
- ▶ Suppose we know how to compute `plus n m`
Then `plus n (succ m)` is

Recursive definitions

Goal: Define `plus n 0`, `plus n 1`, ..., `plus n i`, ... for each `i`

- ▶ `plus n 0 = n`, for every `n`
- ▶ `plus n 1 = succ n = succ (plus n 0)` , for every `n`
- ▶ Suppose we know how to compute `plus n m`
Then `plus n (succ m)` is `succ (plus n m)`

Recursive definitions

Goal: Define `plus n 0`, `plus n 1`, ..., `plus n i`, ... for each `i`

- ▶ `plus n 0 = n`, for every `n`
- ▶ `plus n 1 = succ n = succ (plus n 0)` , for every `n`
- ▶ Suppose we know how to compute `plus n m`
Then `plus n (succ m)` is `succ (plus n m)`

Unravelling the definition yields a computation

Recursive definitions

Goal: Define $\text{plus } n \ 0$, $\text{plus } n \ 1$, \dots , $\text{plus } n \ i$, \dots for each i

- ▶ $\text{plus } n \ 0 = n$, for every n
- ▶ $\text{plus } n \ 1 = \text{succ } n = \text{succ } (\text{plus } n \ 0)$, for every n
- ▶ Suppose we know how to compute $\text{plus } n \ m$
Then $\text{plus } n \ (\text{succ } m)$ is $\text{succ } (\text{plus } n \ m)$

Unravelling the definition yields a computation

- ▶ $\text{plus } 7 \ 3 =$

Recursive definitions

Goal: Define $\text{plus } n \ 0$, $\text{plus } n \ 1$, \dots , $\text{plus } n \ i$, \dots for each i

- ▶ $\text{plus } n \ 0 = n$, for every n
- ▶ $\text{plus } n \ 1 = \text{succ } n = \text{succ } (\text{plus } n \ 0)$, for every n
- ▶ Suppose we know how to compute $\text{plus } n \ m$
Then $\text{plus } n \ (\text{succ } m)$ is $\text{succ } (\text{plus } n \ m)$

Unravelling the definition yields a computation

- ▶ $\text{plus } 7 \ 3 = \text{plus } 7 \ (\text{succ } 2)$

Recursive definitions

Goal: Define $\text{plus } n \ 0$, $\text{plus } n \ 1$, \dots , $\text{plus } n \ i$, \dots for each i

- ▶ $\text{plus } n \ 0 = n$, for every n
- ▶ $\text{plus } n \ 1 = \text{succ } n = \text{succ } (\text{plus } n \ 0)$, for every n
- ▶ Suppose we know how to compute $\text{plus } n \ m$
Then $\text{plus } n \ (\text{succ } m)$ is $\text{succ } (\text{plus } n \ m)$

Unravelling the definition yields a computation

- ▶ $\text{plus } 7 \ 3 = \text{plus } 7 \ (\text{succ } 2)$
 $= \text{succ } (\text{plus } 7 \ 2)$

Recursive definitions

Goal: Define $\text{plus } n \ 0$, $\text{plus } n \ 1$, \dots , $\text{plus } n \ i$, \dots for each i

- ▶ $\text{plus } n \ 0 = n$, for every n
- ▶ $\text{plus } n \ 1 = \text{succ } n = \text{succ } (\text{plus } n \ 0)$, for every n
- ▶ Suppose we know how to compute $\text{plus } n \ m$
Then $\text{plus } n \ (\text{succ } m)$ is $\text{succ } (\text{plus } n \ m)$

Unravelling the definition yields a computation

- ▶ $\text{plus } 7 \ 3 = \text{plus } 7 \ (\text{succ } 2)$
= $\text{succ } (\text{plus } 7 \ 2)$
= $\text{succ } (\text{plus } 7 \ (\text{succ } 1))$

Recursive definitions

Goal: Define `plus n 0`, `plus n 1`, ..., `plus n i`, ... for each `i`

- ▶ `plus n 0 = n`, for every `n`
- ▶ `plus n 1 = succ n = succ (plus n 0)` , for every `n`
- ▶ Suppose we know how to compute `plus n m`
Then `plus n (succ m)` is `succ (plus n m)`

Unravelling the definition yields a computation

- ▶ `plus 7 3 = plus 7 (succ 2)`
= `succ (plus 7 2)`
= `succ (plus 7 (succ 1))`
= `succ (succ (plus 7 1))`
= `succ (succ (plus 7 (succ 0)))`
= `succ (succ (succ (plus 7 0)))`

Recursive definitions

Goal: Define `plus n 0`, `plus n 1`, ..., `plus n i`, ... for each `i`

- ▶ `plus n 0 = n`, for every `n`
- ▶ `plus n 1 = succ n = succ (plus n 0)` , for every `n`
- ▶ Suppose we know how to compute `plus n m`
Then `plus n (succ m)` is `succ (plus n m)`

Unravelling the definition yields a computation

- ▶ `plus 7 3 = plus 7 (succ 2)`
= `succ (plus 7 2)`
= `succ (plus 7 (succ 1))`
= `succ (succ (plus 7 1))`
= `succ (succ (plus 7 (succ 0)))`
= `succ (succ (succ (plus 7 0)))`
= `succ (succ (succ 7)) = succ (succ 8)`
= `succ 9`

Recursive definitions

Goal: Define `plus n 0`, `plus n 1`, ..., `plus n i`, ... for each `i`

- ▶ `plus n 0 = n`, for every `n`
- ▶ `plus n 1 = succ n = succ (plus n 0)` , for every `n`
- ▶ Suppose we know how to compute `plus n m`
Then `plus n (succ m)` is `succ (plus n m)`

Unravelling the definition yields a computation

- ▶ `plus 7 3 = plus 7 (succ 2)`
= `succ (plus 7 2)`
= `succ (plus 7 (succ 1))`
= `succ (succ (plus 7 1))`
= `succ (succ (plus 7 (succ 0)))`
= `succ (succ (succ (plus 7 0)))`
= `succ (succ (succ 7)) = succ (succ 8)`
= `succ 9 = 10`

Recursive definitions . . .

Multiplication is repeated addition

$$\text{mult } n \ m = \underbrace{\text{plus } n \ (\text{plus } n \ (\dots(\text{plus } n \ 0)\dots))}_{m \ \text{times}}$$

Recursive definitions . . .

Multiplication is repeated addition

$$\text{mult } n \ m = \underbrace{\text{plus } n \ (\text{plus } n \ (\dots(\text{plus } n \ 0)\dots))}_{m \text{ times}}$$

The rule for multiplication

- ▶ $\text{mult } n \ 0 = 0$, for all n
- ▶ $\text{mult } n \ (\text{succ } m) = \text{plus } n \ (\text{mult } n \ m)$, for all n and m

Types

Functions operate on values of a fixed type

Types

Functions operate on values of a fixed type

- ▶ `succ` takes a whole number as input and produces a whole number
- ▶ `plus` and `mult` take two whole numbers as input and produce another whole number

Types

Functions operate on values of a fixed type

- ▶ `succ` takes a whole number as input and produces a whole number
- ▶ `plus` and `mult` take two whole numbers as input and produce another whole number

What if we wanted to define `sqrt`, the square root function?

Types

Functions operate on values of a fixed type

- ▶ `succ` takes a whole number as input and produces a whole number
- ▶ `plus` and `mult` take two whole numbers as input and produce another whole number

What if we wanted to define `sqrt`, the square root function?

- ▶ Even if we restrict the input to whole numbers, output will be a real number

Types

Functions operate on values of a fixed type

- ▶ `succ` takes a whole number as input and produces a whole number
- ▶ `plus` and `mult` take two whole numbers as input and produce another whole number

What if we wanted to define `sqrt`, the square root function?

- ▶ Even if we restrict the input to whole numbers, output will be a real number

Other types

- ▶ `capitalize 'a' = 'A', capitalize 'b' = 'B', ...`
- ▶ Inputs and outputs are letters or “characters”

Functional programming

Haskell: a programming language for describing functions

Functional programming

Haskell: a programming language for describing functions

A description in Haskell of a function f has two parts:

1. Types of inputs and outputs
2. Rule for computing the output from the input

Functional programming

Haskell: a programming language for describing functions

A description in Haskell of a function `f` has two parts:

1. Types of inputs and outputs
2. Rule for computing the output from the input

Example:

```
sqr :: Int -> Int    Type definition  
sqr x = x*x          Computation rule
```

Basic types and operations in Haskell

- ▶ `Int` Integers
 - ▶ Operations `+`, `-`, `*`
 - ▶ Functions `div`, `mod`
 - ▶ Note: `/` takes two `Ints` as input and produces a `Float`
- ▶ `Float`
- ▶ `Char`
 - ▶ Values written in single quotes — `'z'`, `'&'`, ...
- ▶ `Bool`
 - ▶ Values `True` and `False`.
 - ▶ Operations `&&`, `||`, `not`

Defining functions

- ▶ Boolean expressions
 - ▶ Comparisons on `Int`: `==`, `/=`, `<`, `<=`, `>`, `>=`
 - ▶ Boolean combinations `&&` (and), `||` (or) and `not` (negation).

Defining functions

- ▶ Boolean expressions
 - ▶ Comparisons on `Int`: `==`, `/=`, `<`, `<=`, `>`, `>=`
 - ▶ Boolean combinations `&&` (and), `||` (or) and `not` (negation).
- ▶ `xor` takes two arguments of `Bool` and checks that exactly one of them is `True`

Defining functions

- ▶ Boolean expressions
 - ▶ Comparisons on `Int`: `==`, `/=`, `<`, `<=`, `>`, `>=`
 - ▶ Boolean combinations `&&` (and), `||` (or) and `not` (negation).
- ▶ `xor` takes two arguments of `Bool` and checks that exactly one of them is `True`

```
xor :: Bool -> Bool -> Bool
xor b1 b2 = (b1 && (not b2)) || ((not b1) && b2)
```

Defining functions

- ▶ Boolean expressions
 - ▶ Comparisons on `Int`: `==`, `/=`, `<`, `<=`, `>`, `>=`
 - ▶ Boolean combinations `&&` (and), `||` (or) and `not` (negation).
- ▶ `xor` takes two arguments of `Bool` and checks that exactly one of them is `True`

```
xor :: Bool -> Bool -> Bool
xor b1 b2 = (b1 && (not b2)) || ((not b1) && b2)
```

- ▶ `inorder` takes three arguments of `Int` and checks that the numbers are in order

Defining functions

- ▶ Boolean expressions
 - ▶ Comparisons on `Int`: `==`, `/=`, `<`, `<=`, `>`, `>=`
 - ▶ Boolean combinations `&&` (and), `||` (or) and `not` (negation).
- ▶ `xor` takes two arguments of `Bool` and checks that exactly one of them is `True`

```
xor :: Bool -> Bool -> Bool
xor b1 b2 = (b1 && (not b2)) || ((not b1) && b2)
```

- ▶ `inorder` takes three arguments of `Int` and checks that the numbers are in order

```
inorder :: Int -> Int -> Int -> Bool
inorder x y z = (x <= y) && (y <= z)
```

Definition by cases: Pattern matching

- ▶ Defining by pattern matching

```
xor :: Bool -> Bool -> Bool
xor True  False = True
xor False True  = True
xor b1    b2    = False
```

Definition by cases: Pattern matching

- ▶ Defining by pattern matching

```
xor :: Bool -> Bool -> Bool
xor True  False = True
xor False True  = True
xor b1    b2    = False
```

- ▶ When does an invocation match a definition?
 - ▶ If definition argument is a constant, the value supplied must be the same constant
 - ▶ If definition argument is a variable, any value supplied matches (and is substituted for that variable)

Definition by cases: Pattern matching

- ▶ Defining by pattern matching

```
xor :: Bool -> Bool -> Bool
xor True  False = True
xor False True  = True
xor b1    b2    = False
```

- ▶ When does an invocation match a definition?
 - ▶ If definition argument is a constant, the value supplied must be the same constant
 - ▶ If definition argument is a variable, any value supplied matches (and is substituted for that variable)
- ▶ Use first definition that matches, top to bottom
- ▶ `xor False True` matches second definition
- ▶ `xor True True` matches third definition

Definition by cases: Pattern matching

- ▶ Can mix variables and constants in patterns

Definition by cases: Pattern matching

- ▶ Can mix variables and constants in patterns

```
or :: Bool -> Bool -> Bool
or True b  = True
or b True  = True
or b1 b2   = False
```

Definition by cases: Pattern matching

- ▶ Can mix variables and constants in patterns

```
or :: Bool -> Bool -> Bool
or True b  = True
or b True  = True
or b1 b2   = False
```

- ▶ `or True False` matches first definition

Definition by cases: Pattern matching

- ▶ Can mix variables and constants in patterns

```
or :: Bool -> Bool -> Bool
or True b  = True
or b True  = True
or b1 b2   = False
```

- ▶ `or True False` matches first definition
- ▶ `or False True` matches second definition

Definition by cases: Pattern matching

- ▶ Can mix variables and constants in patterns

```
or :: Bool -> Bool -> Bool
or True b  = True
or b True  = True
or b1 b2   = False
```

- ▶ `or True False` matches first definition
- ▶ `or False True` matches second definition
- ▶ `or False False` matches third definition

Definition by cases: Pattern matching

```
and :: Bool -> Bool -> Bool
and True b  = b
and False b = False
```

Recursive definitions

- ▶ As we saw earlier, many functions are defined recursively
 - ▶ Base case: Explicit value for $f(0)$
 - ▶ Inductive step: Define $f(n)$ in terms of n and $f(n-1), \dots, f(0)$

Recursive definitions

- ▶ As we saw earlier, many functions are defined recursively
 - ▶ Base case: Explicit value for $f(0)$
 - ▶ Inductive step: Define $f(n)$ in terms of n and $f(n-1), \dots, f(0)$
- ▶ For example, **factorial**
 - ▶ $0! = 1$
 - ▶ $n! = n \cdot (n-1)!$

Recursive definitions

- ▶ As we saw earlier, many functions are defined recursively
 - ▶ Base case: Explicit value for $f(0)$
 - ▶ Inductive step: Define $f(n)$ in terms of n and $f(n-1), \dots, f(0)$
- ▶ For example, **factorial**
 - ▶ $0! = 1$
 - ▶ $n! = n \cdot (n-1)!$

- ▶ In Haskell

```
factorial :: Int -> Int
```

```
factorial 0 = 1
```

```
factorial n = n * (factorial (n-1))
```

Recursive definitions

- ▶ As we saw earlier, many functions are defined recursively
 - ▶ Base case: Explicit value for $f(0)$
 - ▶ Inductive step: Define $f(n)$ in terms of n and $f(n-1), \dots, f(0)$
- ▶ For example, **factorial**
 - ▶ $0! = 1$
 - ▶ $n! = n \cdot (n-1)!$

- ▶ In Haskell

```
factorial :: Int -> Int
```

```
factorial 0 = 1
```

```
factorial n = n * (factorial (n-1))
```

- ▶ Note the bracketing in `factorial (n-1)`
 - ▶ `factorial n-1` would be bracketed as `(factorial n) -1`

Recursive definitions

- ▶ As we saw earlier, many functions are defined recursively
 - ▶ Base case: Explicit value for $f(0)$
 - ▶ Inductive step: Define $f(n)$ in terms of n and $f(n-1), \dots, f(0)$
- ▶ For example, **factorial**
 - ▶ $0! = 1$
 - ▶ $n! = n \cdot (n-1)!$

- ▶ In Haskell

```
factorial :: Int -> Int
factorial 0 = 1
factorial n = n * (factorial (n-1))
```

- ▶ Note the bracketing in `factorial (n-1)`
 - ▶ `factorial n-1` would be bracketed as `(factorial n) -1`
- ▶ No guarantee of termination!
 - ▶ What does `factorial (-1)` generate?

Functions with multiple inputs

`plus m n = m + n`

- ▶ What is the type of `plus`?
 - ▶ Mathematically, $plus : \mathbb{Z} \times \mathbb{Z} \rightarrow \mathbb{Z}$
- ▶ Need to know *arity* of functions

Functions with multiple inputs . . .

- ▶ Assume all functions take only one argument!

Functions with multiple inputs ...


- ▶ Assume all functions take only one argument!

```
plus m n = m + n
```

Functions with multiple inputs ...

- ▶ Assume all functions take only one argument!


`plus m n = m + n`



Functions with multiple inputs ...

- ▶ Assume all functions take only one argument!

`plus m n = m + n`




- ▶ Type of `plus`
 - ▶ `plus m`: input is `Int`, output is `Int`

Functions with multiple inputs ...

- ▶ Assume all functions take only one argument!

`plus m n = m + n`




- ▶ Type of `plus`
 - ▶ `plus m`: input is `Int`, output is `Int`
 - ▶ `plus`: input is `Int`, output is a function `Int -> Int`

Functions with multiple inputs ...

- ▶ Assume all functions take only one argument!


`plus m n = m + n`



- ▶ Type of `plus`
 - ▶ `plus m`: input is `Int`, output is `Int`
 - ▶ `plus`: input is `Int`, output is a function `Int -> Int`
 - ▶ `plus :: Int -> (Int -> Int)`

Functions with multiple inputs ...

► `tplus m n p = m + n + p`



► `tplus m n p :: Int -> (Int -> (Int -> Int))`

Running Haskell programs

- ▶ Write your Haskell program using a text editor
 - ▶ `vi`, `Notepad`, ...
- ▶ Store it in a file with extension `.hs`

Running Haskell programs

- ▶ Write your Haskell program using a text editor
 - ▶ `vi`, `Notepad`, ...
- ▶ Store it in a file with extension `.hs`
- ▶ Use the interactive interpreter `ghci`
- ▶ Within `ghci` you can type the following commands:
 - `:load filename` — Loads a Haskell file
 - `:type expression` — Print the type of a Haskell expression
 - `:quit` — exit from `ghci`
 - `:?` — Print "help" about more `ghci` commands

Running Haskell programs

- ▶ Write your Haskell program using a text editor
 - ▶ `vi`, `Notepad`, ...
- ▶ Store it in a file with extension `.hs`
- ▶ Use the interactive interpreter `ghci`
- ▶ Within `ghci` you can type the following commands:
 - `:load filename` — Loads a Haskell file
 - `:type expression` — Print the type of a Haskell expression
 - `:quit` — exit from `ghci`
 - `:?` — Print "help" about more `ghci` commands
- ▶ Experiment with `ghci` as a "calculator"

Conditional definitions

- ▶ Conditional definitions using guards
- ▶ For instance, “fix” the function to work for negative inputs

```
factorial :: Int -> Int
factorial 0 = 1
factorial n
  | n < 0 = factorial (-n)
  | n > 0 = n * (factorial (n-1))
```

Conditional definitions

- ▶ Conditional definitions using guards
- ▶ For instance, “fix” the function to work for negative inputs

```
factorial :: Int -> Int
factorial 0 = 1
factorial n
  | n < 0 = factorial (-n)
  | n > 0 = n * (factorial (n-1))
```

- ▶ Second definition has two parts
 - ▶ Each part is **guarded** by a condition
 - ▶ Guards are tested top to bottom

Conditional definitions

- ▶ Conditional definitions using guards
- ▶ For instance, “fix” the function to work for negative inputs

```
factorial :: Int -> Int
factorial 0 = 1
factorial n
  | n < 0 = factorial (-n)
  | n > 0 = n * (factorial (n-1))
```

- ▶ Second definition has two parts
 - ▶ Each part is **guarded** by a condition
 - ▶ Guards are tested top to bottom
- ▶ Indentation to show that definition continues on multiple lines

Conditional definitions

- ▶ Conditional definitions using guards
- ▶ For instance, “fix” the function to work for negative inputs

```
factorial :: Int -> Int
factorial 0 = 1
factorial n
  | n < 0 = factorial (-n)
  | n > 0 = n * (factorial (n-1))
```

- ▶ Second definition has two parts
 - ▶ Each part is **guarded** by a condition
 - ▶ Guards are tested top to bottom
- ▶ Indentation to show that definition continues on multiple lines
- ▶ Multiple definitions could have different forms
 - ▶ Pattern matching for `factorial 0`
 - ▶ Conditional definition for `factorial n`

Conditional definitions ...

- ▶ Guards may overlap

```
factorial :: Int -> Int
factorial 0 = 1
factorial n
  | n < 0 = factorial (-n)
  | n > 1 = n * (factorial (n-1))
  | n > 0 = n * (factorial (n-1))
```

Conditional definitions ...

- ▶ Guards may overlap

```
factorial :: Int -> Int
factorial 0 = 1
factorial n
  | n < 0 = factorial (-n)
  | n > 1 = n * (factorial (n-1))
  | n > 0 = n * (factorial (n-1))
```

- ▶ Guards may not cover all cases

```
factorial :: Int -> Int
factorial 0 = 1
factorial n
  | n < 0 = factorial (-n)
  | n > 1 = n * (factorial (n-1))
```

Conditional definitions ...

- ▶ Guards may overlap

```
factorial :: Int -> Int
factorial 0 = 1
factorial n
  | n < 0 = factorial (-n)
  | n > 1 = n * (factorial (n-1))
  | n > 0 = n * (factorial (n-1))
```

- ▶ Guards may not cover all cases

```
factorial :: Int -> Int
factorial 0 = 1
factorial n
  | n < 0 = factorial (-n)
  | n > 1 = n * (factorial (n-1))
```

- ▶ No match for `factorial 1`

```
Program error: pattern match failure: factorial 1
```