

# Introduction to Programming: Lecture 11

K Narayan Kumar

Chennai Mathematical Institute

<http://www.cmi.ac.in/~kumar>

12 Sep 2013

# The binary tree datatype

# The binary tree datatype

```
data Btree a = Nil | Node (Btree a) a (Btree a)
```

# The binary tree datatype

```
data Btree a = Nil | Node (Btree a) a (Btree a)
```

- ▶ `Nil` and `Node` are the constructors.

# The binary tree datatype

```
data Btree a = Nil | Node (Btree a) a (Btree a)
```

- `Nil` and `Node` are the constructors.

```
Node (Node Nil 4 Nil) 6  
      (Node (Node Nil 2 Nil) 3 (Node Nil 5 Nil))
```

# The binary tree datatype

```
data Btree a = Nil | Node (Btree a) a (Btree a)
```

- `Nil` and `Node` are the constructors.

```
Node (Node Nil 4 Nil) 6  
      (Node (Node Nil 2 Nil) 3 (Node Nil 5 Nil))
```



# Levels

- List nodes level by level and from left to right within each level.



# Levels

- List nodes level by level and from left to right within each level.



[4,2,5,1,3]



# Levels

- List nodes level by level and from left to right within each level.



[4,2,5,1,3]

```
mylevels: Btree a -> [[a]]
```

```
mylevels Nil = []
```

```
mylevels (Node tl x tr) =
```

```
  [x]:(join (mylevels tl) (mylevels tr))
```

```
level t = concat (mylevels t)
```

# Levels

- List nodes level by level and from left to right within each level.



[4,2,5,1,3]

```
mylevels: Btree a -> [[a]]
```

```
mylevels Nil = []
```

```
mylevels (Node tl x tr) =
```

```
  [x]:(join (mylevels tl) (mylevels tr))
```



```
level t = concat (mylevels t)
```

# Search trees

- ▶ In a search tree
  - ▶ Values in the left subtree are smaller than the current node
  - ▶ Values in the right subtree are bigger than the current node



# Search trees

- ▶ In a search tree
  - ▶ Values in the left subtree are smaller than the current node
  - ▶ Values in the right subtree are bigger than the current node
- ▶ Two search trees for values [1,2,3,4,5,7]



# Search trees

- ▶ In a search tree
  - ▶ Values in the left subtree are smaller than the current node
  - ▶ Values in the right subtree are bigger than the current node
- ▶ Two search trees for values [1,2,3,4,5,7]





- ▶ Search Trees in Haskell

```
data Ord a => Stree a = Nil | Node (Stree a) a (Stree a)
    deriving (Eq, Show)
```

# Search trees

- ▶ In a search tree
  - ▶ Values in the left subtree are smaller than the current node
  - ▶ Values in the right subtree are bigger than the current node
- ▶ Two search trees for values [1,2,3,4,5,7]



- ▶ Search Trees in Haskell

```
data Ord a => Stree a = Nil | Node (Stree a) a (Stree a)
    deriving (Eq, Show)
```

- ▶ Need `Ord a` to compare values
- ▶ No guarantee of being a search tree!

# Search trees ...

- ▶ Is it a search tree?

# Search trees ...

- Is it a search tree?

```
isstree:: Ord a => (Stree a) -> Bool
isstree Nil = True
isstree (Node tl y tr)
    = (isstree tl) && (isstree tr) &&
      (maxt tl < y) && (y < (mint tr))
```



# Search trees ...

- Is it a search tree?

```
isstree:: Ord a => (Stree a) -> Bool
isstree Nil = True
isstree (Node tl y tr)
    = (isstree tl) && (isstree tr) &&
      (maxt tl < y) && (y < (mint tr))

mint (Node Nil v Nil) = v
mint (Node tl v tr) = min (mint tl) (min v (mint tr))
```

# Search trees ...

- Is it a search tree?


```
isstree:: Ord a => (Stree a) -> Bool
isstree Nil = True
isstree (Node tl y tr)
    = (isstree tl) && (isstree tr) &&
      (maxt tl < y) && (y < (mint tr))

mint (Node Nil v Nil) = v
mint (Node tl v tr) = min (mint tl) (min v (mint tr))
```

- In how many ways is the above program incorrect?


# Search trees ...

- ▶ Searching for a value




# Search trees ...

- ▶ Searching for a value  
Searching for 34




# Search trees ...

- ▶ Searching for a value  
Searching for 34




## Search trees ...

- ▶ Searching for a value  
Searching for 34




# Search trees ...

- ▶ Searching for a value  
Searching for 34



# Search trees ...


- ▶ Searching for a value  
Searching for 49






# Search trees ...

- ▶ Searching for a value  
Searching for 49




# Search trees ...

- ▶ Searching for a value  
Searching for 49



# Search trees ...

- ▶ Searching for a value  
Searching for 49



# Search trees ...

- ▶ Searching for a value  $v$

# Search trees ...

- ▶ Searching for a value  $v$
- ▶ Start at the root

# Search trees ...

- ▶ Searching for a value  $v$
- ▶ Start at the root
- ▶ At each node

# Search trees ...

- ▶ Searching for a value  $v$
- ▶ Start at the root
- ▶ At each node
  - ▶ If the value is found, report Yes

# Search trees ...

- ▶ Searching for a value  $v$
- ▶ Start at the root
- ▶ At each node
  - ▶ If the value is found, report Yes
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, search for  $v$  in left subtree
    - ▶ Otherwise, report No



# Search trees ...

- ▶ Searching for a value  $v$
- ▶ Start at the root
- ▶ At each node
  - ▶ If the value is found, report Yes
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, search for  $v$  in left subtree
    - ▶ Otherwise, report No
  - ▶ If  $v$  is larger than the current value
    - ▶ If right child exists, search for  $v$  in right subtree
    - ▶ Otherwise, report No

# Search trees ...

- ▶ Searching for a value  $v$
- ▶ Start at the root
- ▶ At each node
  - ▶ If the value is found, report Yes
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, search for  $v$  in left subtree
    - ▶ Otherwise, report No
  - ▶ If  $v$  is larger than the current value
    - ▶ If right child exists, search for  $v$  in right subtree
    - ▶ Otherwise, report No
- ▶ Worst case: Number of steps is equal to the longest path from the root to a leaf

# Search trees ...

- ▶ Searching for a value

```
searchtree :: Ord a => (Stree a) -> a -> Bool
```

```
searchtree Nil v = False
```

```
searchtree (Node tl y tr) v
```


```
  | v == y      = True
```

```
  | v < y       = searchtree tl v
```

```
  | otherwise   = searchtree tr v
```

# Search trees, inserting a value


- Insert a value



# Search trees, inserting a value

- Insert a value


Insert 33



# Search trees, inserting a value

- Insert a value


Insert 33



# Search trees, inserting a value

- Insert a value


Insert 33



# Search trees, inserting a value

- Insert a value

Insert 33






# Search trees, inserting a value

- Insert a value


Insert 33



# Search trees, inserting a value

- Insert a value


Insert 48



# Search trees, inserting a value

- Insert a value


Insert 48



# Search trees, inserting a value

- Insert a value


Insert 48



# Search trees, inserting a value

- Insert a value


Insert 48



# Search trees, inserting a value

- Insert a value


Insert 17



# Search trees, inserting a value

- Insert a value


Insert 17



# Search trees, inserting a value

- Insert a value

Insert 17






# Search trees, inserting a value

- Insert a value

Insert 17



## Search trees, inserting a value ...

- ▶ To insert a value  $v$ , find where it should be and add it if it is missing

# Search trees, inserting a value ...

- ▶ To insert a value  $v$ , find where it should be and add it if it is missing
- ▶ Start at the root

# Search trees, inserting a value ...

- ▶ To insert a value  $v$ , find where it should be and add it if it is missing
- ▶ Start at the root
- ▶ At each node

# Search trees, inserting a value ...

- ▶ To insert a value  $v$ , find where it should be and add it if it is missing
- ▶ Start at the root
- ▶ At each node
  - ▶ If the value is found, exit

# Search trees, inserting a value ...

- ▶ To insert a value  $v$ , find where it should be and add it if it is missing
- ▶ Start at the root
- ▶ At each node
  - ▶ If the value is found, exit
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, insert  $v$  in left subtree
    - ▶ Otherwise, add a left child with value  $v$

# Search trees, inserting a value ...

- ▶ To insert a value  $v$ , find where it should be and add it if it is missing
- ▶ Start at the root
- ▶ At each node
  - ▶ If the value is found, exit
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, insert  $v$  in left subtree
    - ▶ Otherwise, add a left child with value  $v$
  - ▶ If  $v$  is larger than the current value
    - ▶ If right child exists, insert  $v$  in right subtree
    - ▶ Otherwise, add a right child with value  $v$

# Search trees, inserting a value ...

- ▶ To insert a value  $v$ , find where it should be and add it if it is missing
- ▶ Start at the root
- ▶ At each node
  - ▶ If the value is found, exit
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, insert  $v$  in left subtree
    - ▶ Otherwise, add a left child with value  $v$
  - ▶ If  $v$  is larger than the current value
    - ▶ If right child exists, insert  $v$  in right subtree
    - ▶ Otherwise, add a right child with value  $v$
- ▶ Worst case: Number of steps is equal to the longest path from the root to a leaf



# Inserting into a search tree

- To insert a value, search for it to identify where it should go

```
inserttree :: Ord a => Stree a -> a -> Stree a
inserttree Nil v = Node Nil v Nil
inserttree (Node tl y tr) v
  | v == y      = Node tl y tr
  | v < y       = Node (inserttree tl v) y tr
  | otherwise   = Node tl y (inserttree tr v)
```

- `inserttree` returns the tree with the value inserted.

# Search trees, deleting a value


- ▶ Deleting  $v$  from a tree

# Search trees, deleting a value

- ▶ Deleting  $v$  from a tree
- ▶ If  $v$  does not match current node, inductively delete from left or right subtree

# Search trees, deleting a value


- ▶ Deleting  $v$  from a tree
- ▶ If  $v$  does not match current node, inductively delete from left or right subtree
- ▶ What if  $v$  does match?



- ▶ What value should replace  $y$ ?

# Search trees, deleting a value


- ▶ Deleting  $v$  from a tree
- ▶ If  $v$  does not match current node, inductively delete from left or right subtree
- ▶ What if  $v$  does match?



- ▶ What value should replace  $y$ ?
- ▶ Cannot blindly shift up  $x$  or  $z$

# Search trees, deleting a value ...


- Delete a value



# Search trees, deleting a value ...

- Delete a value


Delete 41



# Search trees, deleting a value ...

- Delete a value

Delete 41






# Search trees, deleting a value ...

- Delete a value


Delete 41

Cannot shift up 23




# Search trees, deleting a value ...

- ▶ Delete a value  
Delete 41  
Cannot shift up 51




# Search trees, deleting a value ...



- ▶ Cannot blindly shift up **x** or **z**
- ▶ Need to move up a value that is bigger than left and smaller than right
  - ▶ Move up maximum value in left subtree ...
  - ▶ ...or minimum value in right subtree

# Search trees, deleting a value ...


- Delete a value



# Search trees, deleting a value ...

- Delete a value


Delete 41



# Search trees, deleting a value ...

- Delete a value

Delete 41




# Search trees, deleting a value ...

- Delete a value

Delete 41

Remove maximum value in left subtree, 34




# Search trees, deleting a value ...

- Delete a value

Delete 41

Remove maximum value in left subtree, 34

... and use it to replace 41





# Search trees ...


- ▶ Deleting the maximum value in a search tree

# Search trees ...

- ▶ Deleting the maximum value in a search tree
- ▶ Keep going **right** till you run out of values
  - ▶ Rightmost value has no right subtree
  - ▶ Replace rightmost value by its left subtree


# Search trees ...

- ▶ Deleting the maximum value in a search tree
- ▶ Keep going **right** till you run out of values
  - ▶ Rightmost value has no right subtree
  - ▶ Replace rightmost value by its left subtree



# Search trees ...

- ▶ Deleting the maximum value in a search tree
- ▶ Keep going **right** till you run out of values
  - ▶ Rightmost value has no right subtree
  - ▶ Replace rightmost value by its left subtree



## Deleting maximum value in a search tree ...

### ► deletemax

```
deletemax :: Ord a => Stree a -> (a ,Stree a)
```

```
-- We are at rightmost value
```

```
deletemax (Node t1 y Nil) = (y,t1)
```

```
-- We are not yet at rightmost value
```

```
deletemax (Node t1 y t2) = (z, Node t1 y tz)  
  where (z,tz) = deletemax t2
```

# Deleting maximum value in a search tree ...

- ▶ `deletemax`

```
deletemax :: Ord a => Stree a -> (a ,Stree a)
```

```
-- We are at rightmost value
```

```
deletemax (Node t1 y Nil) = (y,t1)
```

```
-- We are not yet at rightmost value
```

```
deletemax (Node t1 y t2) = (z, Node t1 y tz)  
  where (z,tz) = deletemax t2
```

- ▶ Note that `deletemax` returns the maximum value and the modified tree

# Search trees, deleting a value ...

- ▶ To delete a value  $v$

# Search trees, deleting a value ...

- ▶ To delete a value ✓
- ▶ Start at the root



# Search trees, deleting a value ...

- ▶ To delete a value  $v$
- ▶ Start at the root
- ▶ At each node

# Search trees, deleting a value ...

- ▶ To delete a value  $v$
- ▶ Start at the root
- ▶ At each node
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, delete  $v$  from left subtree

# Search trees, deleting a value ...

- ▶ To delete a value  $v$
- ▶ Start at the root
- ▶ At each node
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, delete  $v$  from left subtree
  - ▶ If  $v$  is larger than the current value
    - ▶ If right child exists, delete  $v$  from right subtree

# Search trees, deleting a value ...

- ▶ To delete a value  $v$
- ▶ Start at the root
- ▶ At each node
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, delete  $v$  from left subtree
  - ▶ If  $v$  is larger than the current value
    - ▶ If right child exists, delete  $v$  from right subtree
  - ▶ Otherwise, current value is  $v$ 
    - ▶ If there is no left child, shift up right subtree to current node
    - ▶ If there is a left child
      - Delete maximum value  $x$  from left subtree
      - Replace current value  $v$  by  $x$

# Search trees, deleting a value ...

- ▶ To delete a value  $v$
- ▶ Start at the root
- ▶ At each node
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, delete  $v$  from left subtree
  - ▶ If  $v$  is larger than the current value
    - ▶ If right child exists, delete  $v$  from right subtree
  - ▶ Otherwise, current value is  $v$ 
    - ▶ If there is no left child, shift up right subtree to current node
    - ▶ If there is a left child
      - Delete maximum value  $x$  from left subtree
      - Replace current value  $v$  by  $x$

# Search trees, deleting a value ...

- ▶ To delete a value  $v$
- ▶ Start at the root
- ▶ At each node
  - ▶ If  $v$  is smaller than the current value
    - ▶ If left child exists, delete  $v$  from left subtree
  - ▶ If  $v$  is larger than the current value
    - ▶ If right child exists, delete  $v$  from right subtree
  - ▶ Otherwise, current value is  $v$ 
    - ▶ If there is no left child, shift up right subtree to current node
    - ▶ If there is a left child
      - Delete maximum value  $x$  from left subtree
      - Replace current value  $v$  by  $x$
- ▶ Worst case: Number of steps is equal to the longest path from the root to a leaf

# Deleting from a search tree

- `deletetree` — deletes a given value from the given tree and returns the resulting tree

```
deletetree :: Ord a => Stree a -> a -> Stree a
deletetree Nil v = Nil
deletetree (Node tl y tr) v
  | v < y    = Node (deletetree tl v)  y tr
  | v > y    = Node  tl  y (deletetree tr v)

-- In all cases below, we must have v == y

deletetree (Node Nil y tr) v    = tr
deletetree (Node  tl y tr) v = Node  tx x tr
  where (x,tx) = deletemax tl
```

# Balance

- ▶ The complexity of all the operations depend on the **height** of the tree.




# Balance

- ▶ The complexity of all the operations depend on the **height** of the tree.
- ▶ In general, a search tree will not be balanced

# Balance

- ▶ The complexity of all the operations depend on the **height** of the tree.
- ▶ In general, a search tree will not be balanced
- ▶ Inserting values in ascending or descending order results in highly skewed tree



# Balanced search trees ...

- ▶ Ideally, for each node **size** of left and right subtrees differ by at most one

# Balanced search trees ...

- ▶ Ideally, for each node **size** of left and right subtrees differ by at most one
  - ▶ Height of the tree is logarithmic in size.

# Balanced search trees ...

- ▶ Ideally, for each node **size** of left and right subtrees differ by at most one
  - ▶ Height of the tree is logarithmic in size.

**Lemma:** Let  $T$  be a size balanced tree with  $s$  nodes. The height of  $T$  is at most  $\log(s) + 1$ .

# Balanced search trees ...

- ▶ Ideally, for each node **size** of left and right subtrees differ by at most one
  - ▶ Height of the tree is logarithmic in size.

**Lemma:** Let  $T$  be a size balanced tree with  $s$  nodes. The height of  $T$  is at most  $\log(s) + 1$ .

**Proof:** By induction on the size  $s$ .

# Balanced search trees ...

- ▶ Ideally, for each node **size** of left and right subtrees differ by at most one
  - ▶ Height of the tree is logarithmic in size.

**Lemma:** Let  $T$  be a size balanced tree with  $s$  nodes. The height of  $T$  is at most  $\log(s) + 1$ .

**Proof:** By induction on the size  $s$ .

**Basis:** If  $s = 1$  then the tree has height  $= 1$

# Balanced search trees ...

- ▶ Ideally, for each node **size** of left and right subtrees differ by at most one
  - ▶ Height of the tree is logarithmic in size.

**Lemma:** Let  $T$  be a size balanced tree with  $s$  nodes. The height of  $T$  is at most  $\log(s) + 1$ .

**Proof:** By induction on the size  $s$ .

**Basis:** If  $s = 1$  then the tree has height  $= 1$

**Induction:** Let  $T$  have  $s$  nodes.



# Balanced search trees ...

- ▶ Ideally, for each node **size** of left and right subtrees differ by at most one
  - ▶ Height of the tree is logarithmic in size.

**Lemma:** Let  $T$  be a size balanced tree with  $s$  nodes. The height of  $T$  is at most  $\log(s) + 1$ .

**Proof:** By induction on the size  $s$ .

**Basis:** If  $s = 1$  then the tree has height  $= 1$

**Induction:** Let  $T$  have  $s$  nodes.

Consider the left and right subtrees of this tree.

# Balanced search trees ...

- ▶ Ideally, for each node **size** of left and right subtrees differ by at most one
  - ▶ Height of the tree is logarithmic in size.

**Lemma:** Let  $T$  be a size balanced tree with  $s$  nodes. The height of  $T$  is at most  $\log(s) + 1$ .

**Proof:** By induction on the size  $s$ .

**Basis:** If  $s = 1$  then the tree has height  $= 1$

**Induction:** Let  $T$  have  $s$  nodes.

Consider the left and right subtrees of this tree.

The largest of them has at most  $s/2$  nodes. (Why?)

# Balanced search trees ...

- ▶ Ideally, for each node **size** of left and right subtrees differ by at most one
  - ▶ Height of the tree is logarithmic in size.

**Lemma:** Let  $T$  be a size balanced tree with  $s$  nodes. The height of  $T$  is at most  $\log(s) + 1$ .

**Proof:** By induction on the size  $s$ .

**Basis:** If  $s = 1$  then the tree has height  $= 1$

**Induction:** Let  $T$  have  $s$  nodes.

Consider the left and right subtrees of this tree.

The largest of them has at most  $s/2$  nodes. (Why?)

So, both subtrees have height at most

$$\log(s/2) + 1 = (\log(s) + 1) - 1$$

# Balanced search trees ...

- ▶ Ideally, for each node **size** of left and right subtrees differ by at most one
  - ▶ Height of the tree is logarithmic in size.

**Lemma:** Let  $T$  be a size balanced tree with  $s$  nodes. The height of  $T$  is at most  $\log(s) + 1$ .

**Proof:** By induction on the size  $s$ .

**Basis:** If  $s = 1$  then the tree has height  $= 1$

**Induction:** Let  $T$  have  $s$  nodes.

Consider the left and right subtrees of this tree.

The largest of them has at most  $s/2$  nodes. (Why?)

So, both subtrees have height at most

$$\log(s/2) + 1 = (\log(s) + 1) - 1$$

- ▶ However, it is not easy to maintain size-balance.

# Height-balanced trees

- ▶ Maintain height balanced trees instead of size-balanced trees.
  - ▶ **Height** of left subtree and height of right subtree differ by at most one at any node.


# Height-balanced trees

- ▶ Maintain height balanced trees instead of size-balanced trees.
  - ▶ Height of left subtree and height of right subtree differ by at most one at any node.
- ▶ Height is still logarithmic in size [Adelson-Velskii, Landis]

# Height-balanced trees


- ▶ Maintain height balanced trees instead of size-balanced trees.
  - ▶ Height of left subtree and height of right subtree differ by at most one at any node.
- ▶ Height is still logarithmic in size [Adelson-Velskii, Landis]
- ▶ Somewhat easier to maintain.

# Height balanced trees ...






# Height balanced trees ...



- A height and weight balanced tree.


# Height balanced trees ...



- A height and weight balanced tree.



# Height balanced trees ...



- ▶ A height and weight balanced tree.



- ▶ A height balanced tree that is not weight balanced.

# Height Balanced Trees ...

# Height Balanced Trees ...

- ▶ Let  $S(h)$  be the size of the smallest height balanced tree with height  $h$ .

# Height Balanced Trees ...

- ▶ Let  $S(h)$  be the size of the smallest height balanced tree with height  $h$ .
  - ▶  $S(0) = 0$

# Height Balanced Trees ...

- ▶ Let  $S(h)$  be the size of the smallest height balanced tree with height  $h$ .
  - ▶  $S(0) = 0$
  - ▶  $S(1) = 1$

# Height Balanced Trees ...

- ▶ Let  $S(h)$  be the size of the smallest height balanced tree with height  $h$ .
  - ▶  $S(0) = 0$
  - ▶  $S(1) = 1$
  - ▶  $S(2) = 2$



# Height Balanced Trees ...

- ▶ Let  $S(h)$  be the size of the smallest height balanced tree with height  $h$ .
  - ▶  $S(0) = 0$
  - ▶  $S(1) = 1$
  - ▶  $S(2) = 2$
- ▶ If  $T$  is a height balanced tree of height  $h$ , then one of its two subtrees has height  $h - 1$  and the other has height at least  $h - 2$ . So,

# Height Balanced Trees ...

- ▶ Let  $S(h)$  be the size of the smallest height balanced tree with height  $h$ .
  - ▶  $S(0) = 0$
  - ▶  $S(1) = 1$
  - ▶  $S(2) = 2$
- ▶ If  $T$  is a height balanced tree of height  $h$ , then one of its two subtrees has height  $h - 1$  and the other has height at least  $h - 2$ . So,

$$S(h) \geq S(h - 1) + S(h - 2) + 1$$

# Height Balanced Trees ...

- ▶ Let  $S(h)$  be the size of the smallest height balanced tree with height  $h$ .
  - ▶  $S(0) = 0$
  - ▶  $S(1) = 1$
  - ▶  $S(2) = 2$
- ▶ If  $T$  is a height balanced tree of height  $h$ , then one of its two subtrees has height  $h - 1$  and the other has height at least  $h - 2$ . So,
$$S(h) \geq S(h - 1) + S(h - 2) + 1$$
- ▶ Grows like the Fibonacci numbers, exponentially.

# Height Balanced Trees ...

- ▶ Let  $S(h)$  be the size of the smallest height balanced tree with height  $h$ .
  - ▶  $S(0) = 0$
  - ▶  $S(1) = 1$
  - ▶  $S(2) = 2$
- ▶ If  $T$  is a height balanced tree of height  $h$ , then one of its two subtrees has height  $h - 1$  and the other has height at least  $h - 2$ . So,
$$S(h) \geq S(h - 1) + S(h - 2) + 1$$
- ▶ Grows like the Fibonacci numbers, exponentially.
- ▶  $S(h) \geq 2^{h/1.44}$  or equivalently


$$h(T) \leq 1.44 \log(s(T))$$

# Height Balanced trees ...

- ▶ Use tree rotations to maintain height balance


# Height Balanced trees ...

- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate right



# Height Balanced trees ...


- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate right



- ▶ Useful if  $t_1$  has large height.

# Height Balanced trees ...

- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate right




- ▶ Useful if t1 has large height.
- ▶ `rotateright (Node (Node t1 y t2) x t3) =  
Node t1 y (Node t2 x t3)`



# Balanced search trees ...


- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate left



- ▶ Useful if  $t_3$  has large height.

# Balanced search trees ...


- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate left



- ▶ Useful if  $t_3$  has large height.
- ▶ `rotateleft (Node t1 y (Node t2 x t3)) =`  
`Node (Node t1 y t2) x t3`

# Balanced search trees ...

- ▶ Use tree rotations to maintain height balance
- ▶ Example: rotate left



- ▶ Useful if  $t_3$  has large height.
- ▶ `rotateleft (Node t1 y (Node t2 x t3)) =`  
`Node (Node t1 y t2) x t3`